

What about greaseless crimpers?

Slide bearing technology

- No greasing improves cleanliness of machine and prolongs its lifetime.
- Maximum productivity with very low maintenance costs.
- Flaking cannot stick in grease, no risk of prematurely damaging the crimping head.
- End product can be used in sanitary applications without cleaning.
- 20% more capability for crimping stronger or more difficult couplings versus our competition's equivalent crimpers.
- Consistently accurate crimp result.



HM 200



SC 3



SC 4








SH 4



SH 7

Technical Data	HM 200 Ecoline* HM 200	SC 3 Ecoline*	SC 4 Ecoline* SC 4 Ecoline C.2	SH 4 Ecoline* SH 4 Mobileline	SH 7* SH 7 S**
Crimp force (kN/Ton)	1,300/130	1,200/120	1,800/180	1,800/180	2,400/240; 3,200/320**
4-spiral + 1-pc. fittings	1½"	1½"	2"	2"	2"
4-spiral + 2-pc. fittings	1¼"	1¼"	2"		
4/6-spiral + 2-pc. fittings			1½"	1½" (6-sp 1¼")	1½"
Industry hose	2"	2"	2"	2"	2"
Max. Crimp range (mm)	70	70	70	70	82
Master dies length (mm/inch)	75/2.95	100/3.94	100/3.94	110/4.33	90/3.54
Opening	+30	+35	+35	+27	+24
Type of dies	239	239-xx-Ø	239-xx	239-xx-Ø	239-xx/265
Press path (mm)	8	12	12	12	8
Type of application	Workshop/Mobile	Workshop/Mobile	Workshop/Mobile	Workshop/Mobile	Workshop/Mobile

First-Class Advantages


-  **Greaseless**
Slide bearings on the crimp tool improve efficiency by 20%, reduce friction and help keep the tool free of contaminants.
-  **Universal**
For all types of hoses and fittings.
-  **Ecoline**
High quality for those new to crimping.
-  **Ergonomic**
Ease of use maximizes productivity.
-  **Environment friendly**
Engineered to last.

App compatible



* Abgebildete Maschine. ** Für Ultrahochdruckschläuche.

	SC = Press tool with Cylinder	SH = Hollow piston press tool
No greasing	★★★	★★★
Low maintenance	★★★	★★
Compact	★★	★★★
Light weight	★★	★★★
Accessibility of the workpiece	★★★	★★
Dirt-sensitivity	★★★	★
Sustainable	★★★	★★
Good value	★★	★★★
Well suited for	Workshop	Mobile
Factory warranty in years	3	2



SC 6 | SC 6 S



SH 6



SH 10 i
SH 10 i XL



SC 12 i

SC 6 Ecoline* SC 6	SC 6 S Ecoline SC 6 S	SH 6 Ecoline* SH 6 Mobileline SH 6 S Ecoline SH 6 S Mobileline	SH 10 i Ecoline SH 10 i SH 10 i XL Ecoline SH 10 i XL*	SC 12 i A SC 12 i C.2*
2,000/200	2,800/280	2,400/240; 2,800/280	2,800/280	3,700/370
2"	2"	2"	2"	3"
1½"	2"	1½" / 2"	2"	3"
3"	3"	3"	4"	4"
102	102	102	145	145
110/4.33	110/4.33	110/4.33	126/4.96	126/4.96
+45	+45	+41; +45;	+45; +61	+61
239-xx/266	239-xx/266	239-xx/266	239-xx/237L	239/237L
17	17	12/12/20/20	17	17
Workshop	Workshop/Mobile	Workshop/Mobile	Workshop	Workshop

QDS 239 B

QDC 239.5

Mobile use



Quick and effortless die change with the QDC system.

